SILENT TYPE GENERATOR YX 40



Kode Produk: YX-40

Cooling System : Closed water-cooledStarting Method : D.C 12V or 24V electric startingRated Voltage (V) : 220/380 or 230/400Rated Frequency (Hz) : 50Rated Speed (Rpm) : 1500

Model	YX 40
Rated Power (KW)	40
Rated Power (KVA)	50

Model	YX 40
Rated Voltage (V)	220/380 or 230/400
Rated Frequency (Hz)	50
Engine Model	N4105ZD
Rated Output (KW)	56
Governing Method	mechanical
Bore x Stroke (mm)	100 x 115
Intake Method	Nature
Oil Volume (L)	16
Fuel Consumption (g/kw.h)	246
Fuel Consumption (L/Hr)	16
Oil Consumption (L/Hr)	1.07
Exhaust Flow (L/S)	250
Exhaust Temperature (celsius)	526
Water Volume (L)	25
Cooling System	Closed water-cooled
Starting Method	D.C 12V or 24V electric starting
Alternator Model	224D
Rated Power (kw)	40
Rated Voltage (V)	220/380 or 230/400
Rated Current	76
Rated Frequency (Hz)	50
Rated Speed (Rpm)	1500
Power factor Cos	0.8
Phase Connection	3-phase
Winding Connection	4 wires connected (12 wires for 3 phase)
Excitation Method	Brushless
Insulation Class	Class H
Voltage Regulation	Manual / Automatic
Control Panel	
Net Weight - SILENT (kg)	980
Dimension - SILENT (l x w x h) (m3)	2.25 x 0.93 x 1.17