

SILENT TYPE GENERATOR YX 15

SILENT TYPE GENERATOR YX 15



Kode Produk: YX15-YMKY

Cooling System : Closed water-cooledStarting Method : D.C 12V or 24V electric startingRated Voltage (V) : 220/380 or 230/400Rated Frequency (Hz) : 50Rated Speed (Rpm) : 1500

Model	YX 15
Rated Power (KW)	15
Rated Power (KVA)	20

Model	YX 15
Rated Voltage (V)	220/380 or 230/400
Rated Frequency (Hz)	50
Engine Model	K4100D
Rated Output (KW)	30.1
Governing Method	mechanical
Bore x Stroke (mm)	100 x 115
Intake Method	Nature
Oil Volume (L)	9
Fuel Consumption (g/kw.h)	246
Fuel Consumption (L/Hr)	8.6
Oil Consumption (L/Hr)	1.07
Exhaust Flow (L/S)	101
Exhaust Temperature (celsius)	460
Water Volume (L)	20
Cooling System	Closed water-cooled
Starting Method	D.C 12V or 24V electric starting
Alternator Model	BC184E
Rated Power (kw)	15
Rated Voltage (V)	220/380 or 230/400
Rated Current	28.5
Rated Frequency (Hz)	50
Rated Speed (Rpm)	1500
Power factor Cos	0.8
Phase Connection	3-phase
Winding Connection	4 wires connected (12 wires for 3 phase)
Excitation Method	Brushless
Insulation Class	Class H
Voltage Regulation	Manual / Automatic
Control Panel	
Net Weight - SILENT (kg)	780
Dimension - SILENT (l x w x h) (m3)	2.05 x 0.85 x 1.1